

FUEL TANK FILTERS

Golden Rod Filters



GOLDEN ROD FILTERS

CODE

495 FUEL FILTER

FOR REMOVING MICROSCOPIC PARTICLES (10 MICRONS) OF RUST, SAND, DIRT, SCALE AND LINT AT A 5 GPM GRAVITY FLOW WITH 24" HEAD. FILTER ELEMENT HAS 366 SQ. INCHES OF FILTER SURFACE FOR EFFICIENT ACTION. THIS UNIT WORKS WELL BY ITSELF OR CAN BE PLACED IN COMBINATION WITH THE NO. 496 FUEL FILTER FOR ADDED PROTECTION FROM WATER IN THE FUEL. 9 1/2" HIGH X 4" DIAMETER.

BY USING TWO FILTERS IN COMBINATION, THE BEST POSSIBLE FUEL PROTECTION AVAILABLE CAN BE ACHIEVED. THE GOLDEN ROD FILTERING SYSTEM ENSURES CLEAN, MOISTURE-FREE GASOLINE OR DIESEL FUEL GOES IN THE TANK - EVERY TIME.

150 PSI Working Pressure

496 WATER BLOCK WATER ABSORBING FUEL FILTER

REMOVES WATER FROM GASOLINE AND DIESEL FUEL. 15 MICRON FILTRATION, 5 GPM GRAVITY FLOW WITH 24" HEAD. WATER-ABSORBING POLYMERS TRAP WATER AND RESTRICT FUEL FLOW, WHICH IS YOUR SIGNAL TO REPLACE THE ELEMENT. THIS UNIT WORKS WELL BY ITSELF OR CAN BE PLACED IN COMBINATION WITH NO. 495 FUEL FILTER FOR ADDED PROTECTION AGAINST MICROSCOPIC PARTICLE CONTAMINATION. 9 1/2" HIGH BY 4" DIAMETER.

150 PSI Working Pressure

495 Fuel Filter	CTJ 1800
496 Water Block Filter	CTJ 1809
470-5 Fuel Filter Replacement Element	CTJ 1801
496-5 Water Block Filter Replacement Element	CTJ 1810
470-15 Stainless Steel Strainer Mesh 40	CTJ 1811
470-16 Stainless Steel Strainer Mesh 80	CTJ 1812
491 Fuel Filter Wrench	CTJ 1813
Replacement Bowl Only	CTJ 1802
Replacement Head Only	CTJ 1814