

RPM FUELS

2500 litre site tow banded fuel bowser



Standard specification

- ▶ U.N. approved IBC – fully complies with new regulations
- ▶ Tough all steel construction
- ▶ Lockable cabinet housing pumping equipment
- ▶ ½” BSP generator feed and return connections
- ▶ Rugged site specification with hand brake, ring hitch and flotation tyres
- ▶ Galvanised tubular steel chassis, lifting eyes on tank
- ▶ GPI HP-100 alloy bodied hand pump (flow rate 95 litres/min)
- ▶ 4m hose and trigger
- ▶ Fuel filter with clear plastic bowl, water drain and replaceable element
- ▶ Fully sealed magnetic drive rotary fuel gauge
- ▶ Safety pressure relief valve and automatic suction breather
- ▶ **For use with diesel and gas oil**

Capacity (litres/gallons)	Length (mm)	Width (mm)	Height (mm)	Empty weight (kg)	Full weight (kg)
2500/550	3630	1880	1945	1600	3612

Pump options

GPI HP-100 hand pump (95 litres/min)
12V electric pump (40 litres/min)
12V electric pump (85 litres/min)
24V electric pump (40 litres/min)
24V electric pump (85 litres/min)

Optional extras

K33 3 digit flow meter
K44 4 digit flow meter
Automatic shut-off nozzle (80 litres/min)
12V battery and battery carrier
35 litre spill kit

RPM Fuels & Tanks | 21 Ganges Road . Shotley Gate . Ipswich . Suffolk . IP9 1JR
Tel: 01473 787787 | Fax: 01473 788009 | www.rpm-fuels.co.uk | robert@rpm-fuels.co.uk